

PBAT and PBS Biodegradable Plastics

PBAT or polybutylene adipate terephthalate is a biodegradable random co-polymer (a co-polyester of adipic acid, 1,4-butanediol and terephthalic acid from dimethyl terephthalate). Main advantage of PBAT is that it is a **fully biodegradable alternative to LDPE**, having similar properties including high flexibility and toughness, allowing it to be used for various packaging applications. Biobased content in the polymer can be as high as 50% if 1,4-butanediol (BDO) from renewable sources is used.

Basic production process

PBAT is synthesized from the polymer of 1,4-butanediol and adipic acid and the polymer of dimethyl terephthalate (DMT) with 1,4-butanediol.

Adipic acid and 1,4-butanediol are polymerized to create their polyester (along with water). DMT and 1,4-butanediol are also reacted to form their polyester (along with methanol). This polyester is then added to the butylene adipic acid polyester by using tetrabutoxy titanium (TBOT) as a transesterification catalyst; an overabundance of 1,4-butanediol influences chain lengths. The result is a random co-polymer of the two previously prepared polymers.

Usage

PBAT is marketed commercially as a fully biodegradable plastic. Applications of PBAT include cling wrap for food packaging, compostable plastic bags for gardening and agricultural use, coating for paper cups and plates, water resistant coatings for paperboards etc. Due to its high flexibility and biodegradable nature, PBAT is also marketed as an additive for more rigid biodegradable plastics to impart flexibility while maintaining full biodegradability of the final blend.

Polybutylene Succinate (PBS) is a biodegradable and compostable polyester, which is produced from succinic acid, 1,4-butanediol and a third monomer which is an organic diacid. New biotechnological routes now allow the production of succinic acid based on renewable feedstocks, such as glucose, sucrose and biobased glycerol. The advantage of biobased succinic acid versus the conventional petrochemical route is a significant improvement of the material carbon footprint through the usage of renewable resources. New fermentation production routes now allow for a more cost-competitive production of succinic acid at larger scale. Due to these factors, the market for succinic acid is expected to grow substantially from 40,000 TPA in 2016 by over 10% CAGR over the coming years.

Renewable 1,4-butanediol (BDO from renewable resources) is a liquid, colorless, di-alcohol. Like petro-based BDO and its derivatives, BDO from renewable resources and its derivatives are valuable intermediates in many applications. It is used for producing engineering plastics, biodegradable plastics, polyurethanes and fibers. BDO from renewable resources is produced by fermentation based on renewable feedstocks (such as dextrose) and provides an improved material carbon footprint compared to petrochemically derived BDO.

PBS is a crystalline polyester with a melting temperature exceeding 100°C, which is important for applications that require a high temperature range. PBS has a wide processing/temperature window. PBS grades of different melt flow index (MFI) are available that are suitable for extrusion, injection moulding, thermoforming, fiber spinning and film blowing. PBS processability can be further improved by several compounding strategies while maintaining properties regarding softness and brittleness.

Copolymers of PBS like PBST or Poly (butylene succinate - terephthalate) and PBSA or Poly (butylene succinate - adipate terephthalate) possess good biodegradability along with desirable physical properties. PBS is also blended with other biodegradable and / or bioplastics like PLA or PBAT to produce compounds. Apart from these, other created copolymers include the standard PBS monomers copolymerized with benzyl succinic acid, ethylene glycol, methyl succinic acid.

Unique selling points of PBS

- PBS shows excellent biodegradability, processability and balanced mechanical properties
- High flexibility and heat resistance
- A wide processing window, which makes the resin suitable for extrusion, injection moulding, thermoforming, fibre spinning and film blowing.
- The physical properties and biodegradation rate of PBS materials can be tailored through composition control with different types and various contents of monomers
- PBS can also be readily compounded with other (bio)polymers to tune the performances of the material.
- PBS shows a good binding to natural fibres without any additional bonding agent
- Up to 100% biobased (when using bio-based succinic acid and bio-based 1,4-butanediol), enabling an improved material carbon footprint compared to alternatives based on fossil resources.
- Biodegradable under industrial conditions (EN13432)
- Biobased succinic acid and PBS have a high Biomass Utilization Efficiency (BUE) compared to other biobased building blocks.

Tamil Nadu to ban plastic coated paper cups from January 2019

Hindu Business Line – 26th July 2018

Tamil Nadu has decided to ban LDPE coated paper cups from January 2019. There are over 20 coating units and 500 cup manufacturers in Tamil Nadu only. The market size is estimated to be around 12,000 tons of cups per month in Tamil Nadu alone. The ban is expected to widen to other plastic coated and taken up by other progressive states. (This provides very good opportunity for a bio-degradable plastic like PHAs, BAT, PBS for coating on paper cups, disposable plates& cutlery drinking straws etc.)

As a first step we can prepare a Techno Economic Project Feasibility Report that will provide a realistic picture and help you to take an informed business decision, approach banks for project finance and government departments for statutory approvals. Typical contents of the project feasibility report are:

- 1.0 What are bio-degradable plastics, different types and end applications
- 2.0 What are PBS & PBAT plastics & their different types
- 3.0 Other bio-degradable plastics – their advantages & disadvantages
- 4.0 Suggested production volume & project parameters
- 5.0 Production process & technology
 - 5.1 Production flow diagram
 - 5.2 Chemistry behind the production process
- 6.0 Main plant & machinery with basic specifications and indicative price
- 7.0 Utilities & Support facility with basic specifications and indicative price
- 8.0 Quality Control & Testing Lab with indicative prices
- 9.0 Estimated Project Cost
- 10.0 Manpower requirement & cost
- 11.0 Estimated Product Cost (raw material, additives, production, overheads)
- 12.0 Estimated Turnover, Profitability & Project Payback Period
- 13.0 Working Capital requirement
- 14.0 Factory area & building requirement
- 15.0 Product guiding specifications & test standards
 - 15.1 Product pricing vis-à-vis commodity and other biodegradable plastics
 - 15.2 Product characteristics vis-à-vis commodity and other biodegradable plastics
 - 15.3 Key market segments and end applications
- 16.0 Market Scenario
 - 16.1 Current global production & main players
 - 16.2 Share of bio-degradable plastics in different end application sectors
 - 16.3 Market potential and growth prospects of bioplastics
 - 16.4 Key market segments – volume and growth prospects
- 17.0 Global process technology providers

Once you decide to go ahead we can assist in selection and sourcing manufacturing know-how and develop pilot plant for proof of concept. Thereafter we can assist you to set-up full scale production plant – selection of plant & machinery, plant layout and design, selection of utilities and support equipment, commissioning of plant, sourcing of additives, quality control and testing systems, product technical qualification, target market segments, end application know-how, market intelligence etc.

Best regards,

Dr. ANOMITRA CHAKRAVARTY

Managing Director

KPS Consultants & Impex Pvt. Ltd.

812 Devika Tower, 6 Nehru Place

New Delhi - 110019, India

(M): +91 98993 59661

(T) : +91-11 2621 3885 , 4161 6899

(e) : kpspltd@gmail.com

(w) : www.ksimpex.com

www.linkedin.com/in/anomitra-chakravarty-5a4b1414